








1B2PX – BSP female swivel 60° cone 90° elbow






MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

| Part No. # | DN size | | | | Connection type Thread size  | A mm | B mm | E mm | J mm  | Max. WP MPa  |
|-------------------|---------|------|------|------|---|---------|---------|---------|--|--|
| | mm | inch | mm | inch | | | | | | |
| 1B2PX-4-03 | 5 | -03 | 4.8 | 3/16 | G 1/4 | 48 | 22 | 24 | 17 | 63.0 |
| 1B2PX-4-04 | 6 | -04 | 6.4 | 1/4 | G 1/4 | 59 | 30 | 30 | 17 | 63.0 |
| 1B2PX-6-05 | 8 | -05 | 7.9 | 5/16 | G 3/8 | 59 | 30 | 28 | 22 | 55.0 |
| 1B2PX-6-06 | 10 | -06 | 9.5 | 3/8 | G 3/8 | 60 | 30 | 30 | 22 | 55.0 |
| 1B2PX-8-06 | 10 | -06 | 9.5 | 3/8 | G 1/2 | 60 | 30 | 31 | 27 | 43.0 |
| 1B2PX-8-08 | 12 | -08 | 12.7 | 1/2 | G 1/2 | 74 | 42 | 38 | 27 | 43.0 |
| 1B2PX-12-10 | 16 | -10 | 15.9 | 5/8 | G 3/4 | 84 | 53 | 50 | 32 | 35.0 |
| 1B2PX-12-12 | 20 | -12 | 19.0 | 3/4 | G 3/4 | 100 | 65 | 60 | 32 | 35.0 |
| 1B2PX-20-16 | 25 | -16 | 25.4 | 1 | G 1 1/4 | 100 | 65 | 70 | 50 | 21.0 |

1B4PX – BSP female swivel 60° cone 90° compact elbow



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

| Part No. # | DN size | | | | Connection type Thread size  | A mm | B mm | J mm  | Max. WP MPa  |
|-------------------|---------|------|-----|------|---|---------|---------|--|--|
| | mm | inch | mm | inch | | | | | |
| 1B4PX-4-04 | 6 | -04 | 6.4 | 1/4 | G 1/4 | 45 | 17 | 17 | 63.0 |