


1CAPX – Metric female swivel 24° with O-ring

Light series – Metric swivel nut – ISO 12151-2



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

| Part No. # | DN size | | | | Connection type | | A mm | B mm | J mm | Max. WP MPa |
|----------------------|---------|------|-------------|---------------|-----------------|----|---------|---------|---------|-------------------|
| | mm | inch | Thread size | Tube OD mm | | | | | | |
| 1CAPX-6-03 | 5 | -03 | 4.8 | 3/16 | M12x1.5 | 6 | 45 | 20 | 14 | 31.5 |
| 1CAPX-8-03 | 5 | -03 | 4.8 | 3/16 | M14x1.5 | 8 | 50 | 25 | 17 | 42.5 |
| 1CAPX-6-04 | 6 | -04 | 6.4 | 1/4 | M12x1.5 | 6 | 48 | 20 | 17 | 31.5 |
| 1CAPX-8-04 | 6 | -04 | 6.4 | 1/4 | M14x1.5 | 8 | 51 | 23 | 17 | 42.5 |
| 1CAPX-10-04 | 6 | -04 | 6.4 | 1/4 | M16x1.5 | 10 | 50 | 22 | 19 | 40.0 |
| 1CAPX-10-05 | 8 | -05 | 7.9 | 5/16 | M16x1.5 | 10 | 50 | 22 | 19 | 40.0 |
| 1CAPX-12-05 | 8 | -05 | 7.9 | 5/16 | M18x1.5 | 12 | 50 | 22 | 22 | 35.0 |
| 1CAPX-10-06 | 10 | -06 | 9.5 | 3/8 | M16x1.5 | 10 | 51 | 22 | 22 | 40.0 |
| 1CAPX-12-06 | 10 | -06 | 9.5 | 3/8 | M18x1.5 | 12 | 52 | 23 | 22 | 35.0 |
| 1CAPX-15-08 | 12 | -08 | 12.7 | 1/2 | M22x1.5 | 15 | 59 | 28 | 27 | 31.5 |
| 1CAPX-18-08 | 12 | -08 | 12.7 | 1/2 | M26x1.5 | 18 | 57 | 26 | 32 | 31.5 |
| 1CAPX-18-10 | 16 | -10 | 15.9 | 5/8 | M26x1.5 | 18 | 56 | 25 | 32 | 31.5 |
| 1CAPX-22-12 | 20 | -12 | 19.0 | 3/4 | M30x2 | 22 | 62 | 27 | 36 | 28.0 |
| 1CAPX-28-16 | 25 | -16 | 25.4 | 1 | M36x2 | 28 | 64 | 29 | 41 | 21.0 |