



## 1B258 – BSP female swivel 60° cone 90° elbow



**MATERIAL** Galvanised steel with transparent Cr(VI)-free plating.  
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Tube OD inch							
1B258-4-4	6	-04	6.4	1/4	G 1/4	1/4	64	32	28	19	63.0
1B258-6-5	8	-05	7.9	5/16	G 3/8	3/8	65	33	30	22	55.0
1B258-6-6	10	-06	9.5	3/8	G 3/8	3/8	73	36	33	22	55.0
1B258-8-8	12	-08	12.7	1/2	G 1/2	1/2	82	41	40	27	43.0
1B258-10-8	12	-08	12.7	1/2	G 5/8	5/8	82	41	38	30	37.5
1B258-12-12	20	-12	19.0	3/4	G 3/4	3/4	100	54	53	32	35.0
1B258-16-16	25	-16	25.4	1	G 1	1	127	67	65	41	28.0

## 1D958 – BSP male DIN 3852 Form A



**MATERIAL** Galvanised steel with transparent Cr(VI)-free plating.  
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	H mm	Max. WP MPa
	mm	inch	Thread size	Tube OD inch						
1D958-4-4	6	-04	6.4	1/4	G 1/4	1/4	58	26	19	63.0
1D958-6-5	8	-05	7.9	5/16	G 3/8	3/8	59	27	22	55.0
1D958-6-6	10	-06	9.5	3/8	G 3/8	3/8	64	27	22	55.0
1D958-8-8	12	-08	12.7	1/2	G 1/2	1/2	72	31	27	43.0
1D958-12-12	20	-12	19.0	3/4	G 3/4	3/4	80	34	32	35.0
1D958-16-16	25	-16	25.4	1	G 1	1	95	35	41	28.0