

## 2030T – PTFE hose



### MAIN FEATURES

- Suitable for high temperatures
- Inert to virtually all hydraulic and chemical fluids

### APPLICATIONS

Medium pressure service for use with hydraulic fluids at high temperatures and aggressive chemicals in the chemical industry, surface engineering, 2-component systems.

The core tube material conforms to FDA 21 CFR177.1550.

### CONSTRUCTION

**Core tube** : Polytetrafluoroethylene  
**Pressure reinforcement** : One braided layer of stainless steel wire

**Cover** : -  
**Colour** : -

### TEMPERATURE RANGE

-50°C up to +150°C permanent temperature  
 +230°C at working pressures up to 2 MPa

[Visit the webpage](#)

Part No.  #	DN	size	mm		mm	Max. working pressure MPa / psi		Min. burst pressure MPa / psi		Min. bend radius mm	Weight kg/m	Fittings
			mm	inch		MPa	psi	MPa	psi			
2030T-03V70	5	-03	4.7	3/16	7.8	27.5	3,985	110.0	15,950	50	0.09	YX
2030T-04V70	6	-04	6.3	1/4	9.5	24.0	3,480	96.0	13,920	75	0.13	YX
2030T-05V70	8	-05	8.2	5/16	11.5	20.0	2,900	80.0	11,600	100	0.17	YX
2030T-06V70	10	-06	9.7	3/8	13.0	17.5	2,535	70.0	10,150	120	0.19	YX
2030T-08V70	12	-08	12.8	1/2	16.7	15.0	2,175	60.0	8,700	135	0.29	YX
2030T-10V70	16	-10	16.0	5/8	20.0	12.5	1,810	50.0	7,250	160	0.34	YX
2030T-12V70	20	-12	19.4	3/4	23.5	10.0	1,450	40.0	5,800	200	0.41	YX
2030T-16V70	25	-16	25.0	1	29.0	8.0	1,160	32.0	4,640	250	0.51	YX

### NOTES

- Not recommended for dynamic applications.
- Convuluted version on request