


# LF 3000® Push-In Fittings / Stud Fittings

## 3193 Stud Run Tee, Male BSPP and Metric Thread

Technical polymer, Nickel-plated brass, NBR




ØD	C		E	F	G	H	H1	L	Kg
4	M5x0.8	<b>3193 04 19</b>	3.5	8	8.5	26	11.5	14.5	0.003
	G1/8	<b>3193 04 10</b>	5	13	8.5	23	8.5	14.5	0.006
	G1/4	<b>3193 04 13</b>	5.5	16	8.5	23	8.5	14.5	0.011
6	M5x0.8	<b>3193 06 19</b>	3.5	8	10.5	29.5	12.5	17.5	0.004
	G1/8	<b>3193 06 10</b>	5	13	10.5	27	10	17.5	0.007
	G1/4	<b>3193 06 13</b>	5.5	16	10.5	27	10	17.5	0.012
8	G1/8	<b>3193 08 10</b>	4.5	13	13.5	36.5	14	23	0.011
	G1/4	<b>3193 08 13</b>	5.5	16	13.5	34.5	12	23	0.014
	G3/8	<b>3193 08 17</b>	5.5	20	13.5	34.5	12	23	0.019
10	G1/4	<b>3193 10 13</b>	5.5	16	16	42	15.5	26.5	0.017
	G3/8	<b>3193 10 17</b>	5.5	20	16	40.5	14	26.5	0.020
	G1/2	<b>3193 10 21</b>	7	24	16	40.5	14	26.5	0.029
12	G1/4	<b>3193 12 13</b>	5.5	16	19	48	17	31	0.021
	G3/8	<b>3193 12 17</b>	5.5	20	19	46.5	15.5	31	0.024
	G1/2	<b>3193 12 21</b>	7	24	19	46.5	15.5	31	0.033
14	G3/8	<b>3193 14 17</b>	5.5	20	22	56.5	21.5	35.5	0.036
	G1/2	<b>3193 14 21</b>	7	24	22	51	16	35.5	0.036
	G3/8	<b>3193 16 17</b>	7.5	27	27	79.5	41	38.5	0.121
16	G1/2	<b>3193 16 21</b>	9	27	27	79.5	41	38.5	0.117

The body swivels for positioning purposes.

## 3158 Y Piece, Male BSPP and Metric Thread

Technical polymer, Nickel-plated brass, NBR




ØD	C		E	F	H	K	L	N	Kg
4	M5x0.8	<b>3158 04 19</b>	3.5	8	32.5	8.5	17.5	9	0.006
	M5x0.8	<b>3158 06 19</b>	3.5	10	39.5	10.5	21.5	11	0.009
6	G1/8	<b>3158 06 10</b>	5	13	39	10.5	21.5	11	0.012
	G1/4	<b>3158 06 13</b>	5.5	16	39.5	10.5	21.5	11	0.017
8	G1/8	<b>3158 08 10</b>	5	13	49	13.5	28	14.5	0.020
	G1/4	<b>3158 08 13</b>	5.5	16	49.5	13.5	28	14.5	0.023
	G3/8	<b>3158 08 17</b>	6	19	48	13.5	28	14.5	0.031
10	G1/4	<b>3158 10 13</b>	5.5	16	58	16	33	17	0.032
	G3/8	<b>3158 10 17</b>	6	20	57.5	16	33	17	0.040
12	G1/2	<b>3158 10 21</b>	7	24	58	16	33	17	0.054
	G3/8	<b>3158 12 17</b>	6	20	62	19	39	20	0.044
	G1/2	<b>3158 12 21</b>	7	24	63	19	39	20	0.050

The body swivels for positioning purposes.

## 3132 Double Y, Male BSPP Thread

Technical polymer, Nickel-plated brass, NBR




ØD	C		E	F	H	K	K1	N	N1	ØT	Kg
4	G1/8	<b>3132 04 10</b>	5	13	41	25.5	21	10	8.5	3.7	0.022
	G1/4	<b>3132 04 13</b>	5.5	16	40	25.5	21	10	8.5	3.7	0.026
6	G1/8	<b>3132 06 10</b>	5	19	53.5	31.5	26.5	12	10	3.7	0.041
	G1/4	<b>3132 06 13</b>	5.5	19	52.5	31.5	26.5	12	10	3.7	0.042

The body swivels for positioning purposes.

## 3148 Y Piece, Male BSPT Thread

Technical polymer, Nickel-plated brass, NBR



ØD	C		F	H	K	L	N	Kg
4	R1/8	<b>3148 04 10</b>	10	32.5	8.5	17.5	9	0.009
	R1/4	<b>3148 04 13</b>	14	33	8.5	17.5	9	0.018
6	R1/8	<b>3148 06 10</b>	10	39.5	10.5	21.5	11	0.012
	R1/4	<b>3148 06 13</b>	14	40	10.5	21.5	11	0.021
8	R1/8	<b>3148 08 10</b>	13	56.5	13.5	28	14.5	0.020
	R1/4	<b>3148 08 13</b>	14	55.5	13.5	28	14.5	0.025
	R3/8	<b>3148 08 17</b>	16	48.5	13.5	28	14.5	0.034
10	R1/4	<b>3148 10 13</b>	14	60	19	39	20	0.033
	R3/8	<b>3148 10 17</b>	16	60.5	19	39	20	0.043
	R1/2	<b>3148 10 21</b>	24	61	19	39	20	0.062
12	R3/8	<b>3148 12 17</b>	19	66	19	39	20	0.054
	R1/2	<b>3148 12 21</b>	21	66	19	39	20	0.059

Pre-coated thread

The body swivels for positioning purposes.