


# LF 3800 Push-In Fittings / Stud Fittings

## 3800 Cartridge

Stainless steel 316L, FKM




ØD		G	G1	H	H1	H2	N	Kg
4	<b>3800 04 00</b>	9.8	8	17	8.5	8.5	11	0.006
6	<b>3800 06 00</b>	12.1	10	19	10.5	8.5	13.5	0.008
8	<b>3800 08 00</b>	14.8	13	21	12.5	8.5	16	0.012
10	<b>3800 10 00</b>	17.5	15	24.5	14	10.5	20	0.019

Cavity dimensions available on request

## 3809 Stud Elbow, Male BSPT Thread

Stainless steel 316L, FKM




ØD	C	F	G	H	L	Kg
4	R1/8 <b>3809 04 10</b>	10	10	23.5	16.5	0.020
	R1/8 <b>3809 06 10</b>	13	12	27.5	20	0.030
6	R1/4 <b>3809 06 13</b>	14	12	27.5	25	0.036
	R1/8 <b>3809 08 10</b>	14	15	32	25	0.040
8	R1/4 <b>3809 08 13</b>	14	14.5	34	25	0.045
	R1/4 <b>3809 10 13</b>	19	17.5	37.5	27.5	0.068
10	R3/8 <b>3809 10 17</b>	19	17.5	37.5	27.5	0.069

The body swivels for positioning purposes.

## 3809 Stud Elbow, Male NPT Thread

Stainless steel 316L, FKM




ØD	C	F	G	H	L	Kg
6	NPT1/8 <b>3809 06 11</b>	13	12.5	29	22.5	0.031
	NPT1/4 <b>3809 06 14</b>	14	12.5	29	22.5	0.036
8	NPT1/8 <b>3809 08 11</b>	14	15	34	24	0.040
	NPT1/4 <b>3809 08 14</b>	14	15	34	24	0.045
10	NPT1/4 <b>3809 10 14</b>	19	17.5	39.5	30	0.068
	NPT3/8 <b>3809 10 18</b>	19	17.5	39.5	30	0.071

The body swivels for positioning purposes.

## 3899 Stud Elbow, Male BSPP and Metric Thread

Stainless steel 316L, FKM




ØD	C	F	G	H	L	Kg
4	M5x0.8 <b>3899 04 19</b>	10	10	26	18	0.020
	G1/8 <b>3899 04 10</b>	13	10	27	19	0.022
	G1/4 <b>3899 04 13</b>	17	10	27	19	0.018
6	M5x0.8 <b>3899 06 19</b>	13	12	33	24	0.031
	G1/8 <b>3899 06 10</b>	6	12	33	24	0.031
	G1/4 <b>3899 06 13</b>	17	12	32	24	0.036
8	G1/8 <b>3899 08 10</b>	14	15	35	25	0.039
	G1/4 <b>3899 08 13</b>	17	15	35	25	0.044
	G3/8 <b>3899 08 17</b>	21	15	34.5	25	0.048
10	G1/4 <b>3899 10 13</b>	19	17	43	31	0.069
	G3/8 <b>3899 10 17</b>	21	17	42	31	0.072

The body swivels for positioning purposes.

## 3889 Compact Stud Elbow, Male BSPT Thread

Stainless steel 316L, FKM




ØD	C	F	G	H	L	Kg
4	R1/8 <b>3889 04 10</b>	13	10	18	17	0.019
	R1/4 <b>3889 04 13</b>	17	10	19.5	16.5	0.018
6	R1/8 <b>3889 06 10</b>	13	12	21.5	20.5	0.025
	R1/4 <b>3889 06 13</b>	14	12	21.5	20.5	0.032
8	R1/8 <b>3889 08 10</b>	14	15	24	22	0.036
	R1/4 <b>3889 08 13</b>	14	15	24	22	0.036
10	R1/4 <b>3889 10 13</b>	17	17.5	28.5	27.5	0.058
	R3/8 <b>3889 10 17</b>	19	17.5	28.5	27.5	0.068
12	R1/4 <b>3889 12 13</b>	22	20	33.5	30	0.088
	R3/8 <b>3889 12 17</b>	22	20	33.5	30	0.090
	R1/2 <b>3889 12 21</b>	22	20	33.5	33	0.097

The body swivels for positioning purposes. Max. 20 bar

## 3889 Compact Male Stud Elbow, Male NPT Thread

Stainless steel 316L, FKM



ØD	C	F	G	H	L	Kg
4	NPT1/8 <b>3889 04 11</b>	13	10	17.5	19	0.019
6	NPT1/8 <b>3889 06 11</b>	13	12.5	20	22.5	0.026
	NPT1/4 <b>3889 06 14</b>	14	12.5	20	22.5	0.033
8	NPT1/8 <b>3889 08 11</b>	13	15	25	24	0.036
	NPT1/4 <b>3889 08 14</b>	14	15	24	24	0.036
10	NPT1/4 <b>3889 10 14</b>	17	17.5	27.5	27.5	0.059
	NPT3/8 <b>3889 10 18</b>	19	17.5	28.5	26.5	0.068
12	NPT1/4 <b>3889 12 14</b>	22	20	31.5	32.5	0.086
	NPT3/8 <b>3889 12 18</b>	22	20	32.5	32.5	0.089
	NPT1/2 <b>3889 12 22</b>	22	20	27.5	32.5	0.098

The body swivels for positioning purposes. Max. 20 bar