


LF 3800 Push-In Fittings / Stud Fittings

3805 Stud Fitting, Male NPT Thread

Inch

Stainless steel 316L, FKM




ØD	C		F	F1	H	Kg
3/16	NPT1/8	3805 55 11	10	3	15.5	0.010
	NPT1/8	3805 56 11	13	4	19	0.012
1/4	NPT1/4	3805 56 14	14	4	17.5	0.017
	NPT1/4	3805 60 14	19	6	25	0.029
3/8	NPT3/8	3805 60 18	19	7	24	0.031
	NPT1/4	3805 62 14	22	7	26	0.036
1/2	NPT3/8	3805 62 18	22	8	25	0.041
	NPT1/2	3805 62 22	22	10	25	0.049

5/32" (4 mm) and 5/16" (8 mm) also available

3801 Stud Fitting, Male BSPP and Metric Thread


Stainless steel 316L, FKM



ØD	C		F	F1	H	Kg
4	M5x0.8	3801 04 19	10	2.5	17	0.005
	G1/8	3801 04 10	13	3	16.5	0.009
6	M5x0.8	3801 06 19	13	2.5	20.5	0.010
	G1/8	3801 06 10	13	4	18	0.010
8	G1/4	3801 06 13	17	4	18	0.015
	G1/8	3801 08 10	15	5	19	0.013
10	G1/4	3801 08 13	17	5	20.5	0.017
	G3/8	3801 08 17	21	6	20	0.027
12	G1/4	3801 10 13	19	7	25	0.025
	G3/8	3801 10 17	21	7	25	0.034
12	G1/4	3801 12 13	21	7	27	0.030
	G3/8	3801 12 17	21	9	26.5	0.034

3821 Stud Standpipe, Male BSPT Thread


Stainless steel 316L



ØD	C		F	H	Kg
4	R1/8	3821 04 10	10	21	0.006
	R1/8	3821 06 10	10	23	0.007
6	R1/4	3821 06 13	14	24	0.015
	R1/8	3821 08 10	11	24	0.008
8	R1/4	3821 08 13	14	25	0.016
	R1/4	3821 10 13	19	30	0.017
10	R3/8	3821 10 17	19	30	0.022
	R1/4	3821 12 13	19	31	0.017
12	R3/8	3821 12 17	19	31	0.022
	R1/2	3821 12 21	22	32	0.037

3821 Stud Standpipe, Male NPT Thread

Stainless steel 316L




ØD	C		F	H	Kg
4	NPT1/8	3821 04 11	10	21	0.006
	NPT1/8	3821 06 11	10	23	0.007
6	NPT1/4	3821 06 14	14	24	0.016
	NPT1/8	3821 08 11	14	24	0.008
8	NPT1/4	3821 08 14	14	25	0.016
	NPT1/4	3821 10 14	14	30	0.018
10	NPT3/8	3821 10 18	17	30	0.010
	NPT1/4	3821 12 14	14	31	0.018

3821 Stud Standpipe, Male NPT Thread

Inch

Stainless steel 316L




ØD	C		F	H	Kg
1/4	NPT1/8	3821 56 11	10	26	0.009
	NPT1/4	3821 56 14	14	27	0.016
3/8	NPT1/4	3821 60 14	19	32	0.018
	NPT3/8	3821 60 18	19	32	0.028
1/2	NPT1/4	3821 62 14	19	36	0.020
	NPT3/8	3821 62 18	19	37	0.025
1/2	NPT1/2	3821 62 22	22	37	0.042

5/32" (4 mm) and 5/16" (8 mm) also available

3831 Stud Standpipe, Male BSPP and Metric Thread

Stainless steel 316L, FKM



ØD	C		F	H	Kg
4	M5x0.8	3831 04 19	10	23.5	0.004
	G1/8	3831 04 10	13	22	0.008
6	G1/8	3831 06 10	13	24	0.009
	G1/4	3831 06 13	17	24	0.015
8	G1/8	3831 08 10	13	25	0.010
	G1/4	3831 08 13	17	27	0.019
10	G3/8	3831 08 17	21	27	0.024
	G1/4	3831 10 13	17	32	0.021
12	G3/8	3831 10 17	21	32	0.025
	G1/4	3831 12 13	17	33	0.021
12	G3/8	3831 12 17	21	33	0.028
	G1/2	3831 12 21	24	36	0.043

Stud standpipe 3821 and 3831 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required

