




Female ORFS Swivel

23.4414.

ISO 12151-1 / ISO 8434-3 / SAE J516



REFERENCE	hose dash	hose Ø inch	thread inch	C cut off mm	HEX mm
23.4414.0404	-4	1/4"	9/16" - 18	20.0	17
23.4414.0406	-4	1/4"	11/16" - 16	23.2	22
23.4414.0506	-5	5/16"	11/16" - 16	23.5	22
23.4414.0606	-6	3/8"	11/16" - 16	24.5	22
23.4414.0608	-6	3/8"	13/16" - 16	25.0	24
23.4414.0808	-8	1/2"	13/16" - 16	26.5	24
23.4414.0810	-8	1/2"	1" - 14	29.5	30
23.4414.0812	-8	1/2"	1.3/16" - 14	30.5	36
23.4414.1008	-10	5/8"	13/16" - 16	29.0	24
23.4414.1010	-10	5/8"	1" - 14	30.9	30
23.4414.1012	-10	5/8"	1.3/16" - 14	30.6	36
23.4414.1210	-12	3/4"	1" - 14	33.2	30
23.4414.1212	-12	3/4"	1.3/16" - 14	31.7	36
23.4414.1216	-12	3/4"	1.7/16" - 12	34.7	41
23.4414.1616	-16	1"	1.7/16" - 12	34.1	41
23.4414.1620	-16	1"	1.11/16" - 12	34.0	50
23.4414.2020	-20	1.1/4"	1.11/16" - 12	36.5	50
23.4414.2024	-20	1.1/4"	2" - 12	36.5	50
23.4414.2424	-24	1.1/2"	2" - 12	36.0	60

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating / ROHS compliant

VERSIONS: Stainless Steel (add an 'S' at the end of the REFERENCE)