



SUPERSTEAM RED



EN ISO 6134 Type 2 Class A (Q) 1.8 MPa / 270 PSI WP – 10.1260.R

Saturated Steam steel braid hose +210°C (+410°F)

#	inch	ID		OD		MPa		PSI		MIN BEND RAD
		mm	mm	mm	mm	MPa	PSI	MPa	PSI	
10.1260.08R	1/2"	12,7	24,00	1,8	270	18,0	2700	150		
10.1260.12R	3/4"	19,0	33,00	1,8	270	18,0	2700	230		
10.1260.16R	1"	25,4	39,00	1,8	270	18,0	2700	300		
10.1260.20R	1.1/4"	31,8	47,00	1,8	270	18,0	2700	375		
10.1260.24R	1.1/2"	38,1	53,00	1,8	270	18,0	2700	455		
10.1260.32R	2"	50,8	68,00	1,8	270	18,0	2700	600		
10.1260.40R	2.1/2"	63,0	83,00	1,8	270	18,0	2700	675		
10.1260.48R	3"	76,0	98,00	1,8	270	18,0	2700	725		

INNER TUBE: black, heat resistance synthetic rubber
REINFORCEMENT: high tensile steel wire braids

OUTER TUBE: red, heat, weather and abrasion resistant synthetic rubber
SAFETY FACTOR: 10:1

APPLICATION: super heated steam services in chemical plants, steel mills, refineries, shipyards

TEMPERATURE RANGE: -40°C (-40°F) +210°C (+410°F)
NOTE: For longer life, drain after use

BALFLEX / SUPERSTEAM EN ISO 6134 Type 2 CLASS A (Q) - 210°C / 410°F - DN12 - 1/2" - WP 1.8 MPa / 270 PSI

LPG DELIVERY HOSE



LPG 2.5MPa / 350PSI hose – 10.1214.

Liquefied Petroleum Gas delivery hose, long length.

#	inch	ID		OD		MPa		PSI		MIN BEND RAD
		mm	mm	mm	mm	MPa	PSI	MPa	PSI	
10.1214.04	1/4"	6,0	15,0	2,5	370	7,5	1100	100		
10.1214.05	5/16"	8,0	16,0	2,5	370	7,5	1100	114		
10.1214.06	3/8"	9,5	19,0	2,5	370	7,5	1100	127		
10.1214.08	1/2"	12,7	23,00	2,5	370	7,5	1100	178		
10.1214.12	3/4"	19,0	31,00	2,5	370	7,5	1100	240		
10.1214.16	1"	25,4	38,00	2,5	370	7,5	1100	300		
10.1214.20	1.1/4"	32,0	45,00	2,5	370	7,5	1100	419		
10.1214.24	1.1/2"	38,0	52,00	2,5	370	7,5	1100	500		
10.1214.32	2"	50,8	67,00	2,5	370	7,5	1100	630		

INNER TUBE: seamless synthetic rubber resistant to LPG
REINFORCEMENT: 2 high resistance synthetic fiber braid

OUTER TUBE: black wrapped, smooth, weather and abrasion resistant synthetic rubber
SAFETY FACTOR: 3:1

APPLICATION: LPG (Liquefied Petroleum Gas)

TEMPERATURE RANGE: -30°C (-22°F) +100°C (+212°F)

BALFLEX / LPG / GPL DIN EN 1762 - 1/4" - MAX WP 2.5 MPa / 350 PSI