

# AQUACONN SP 10



## APPLICATION - ANWENDUNG - USO - APPLICATION

[EN] water suction and discharge in industrial and construction services.

[DE] saug & druckschlauch zur verwendung in industrie und baubranche.

[ES] para el suministro y aspiracion de agua para el sector de la construcción e industria

[FR] pour aspiration et refoulement d'eau dans l'industrie et construction.l'agriculture



## STRUCTURE - AUFBAU - ESTRUCTURA - STRUCTURE

[EN] **TUBE:** natural and synthetic rubber.

**REINFORCEMENT:** high tensile synthetic textile and steel helix wire.

**COVER:** abrasion and weather resistant synthetic rubber.

**SURFACE:** smooth with fabric impression.

[DE] **SEELE:** natur- und synthetischer kautschuk.

**EINLAGE:** hochzugfeste synthetische einlage mit stahldrahteinlage.

**DECKE:** wetter- und abriebfester syntethischer gummi.

**OBERFLÄCHE:** stoffimpression

[ES] **SUSTRATO:** caucho natural y sintético.

**REFUERZO:** inserciones textiles con alta resistencia con espiral en acero.

**COBERTURA:** en caucho sintetico resistente a los agentes atmosféricos.

**SUPERFICIE:** con impresión de tela

[FR] **TUBE:** caoutchouc naturel et synthétique.

**RENFORCEMENT:** insertion textile haute tenacite et spirale en acier noyee

**RETEMENT:** caoutchouc synthétique resistant a l'abrasion et aux agents atmospheriques.

**SURFACE:** impression textile



mm	mm	bar	bar	bar	gr/mt	mm	mt
19	29	10	30	0,8	575	152	40
25	36	10	30	0,8	741	200	40
30	41	10	30	0,8	909	240	40
32	43	10	30	0,8	961	256	40
35	46	10	30	0,8	1038	280	40
38	49	10	30	0,8	1240	304	40
40	51	10	30	0,8	1337	320	40
42	52	10	30	0,8	1380	336	40
45	57	10	30	0,8	1490	360	40
50	63	10	30	0,8	1745	408	40
60	73	10	30	0,8	2156	480	40
63	76	10	30	0,8	2325	504	40
70	84	10	30	0,8	2741	560	40
76	90	10	30	0,8	2963	608	40
80	94	10	30	0,8	3099	640	20/40
90	102	10	30	0,8	4238	720	20/40
100	114	10	30	0,8	4186	816	20
102	114	10	30	0,8	4186	816	20/40
110	126	10	30	0,8	4660	880	20
120	138	10	30	0,8	5981	960	20
127	144	10	30	0,8	5418	1016	20
150	172	10	30	0,8	8550	1216	20



## RECOMMENDED CLAMP/COLLAR - EMPFOHLENE KLAMMER/KRAGEN - ABRAZADERA/COLLAR RECOMENDADO - COLLIER/COLLIER RECOMMANDÉ

STF – hose clamp with screw / STC – hose clamp with bolt



-25°C / +70°  
-13°F / +158°F



**NORMS:** ISO 1307

**MARKING:** EUROCORD® WATER  
SUCTION/DELIVERY HOSE W.P. 10 BAR