

# PRESSCONN GREEN FUEL



## APPLICATION - ANWENDUNG - USO - APPLICATION

[EN] suitable for delivery of industrial oils and fuels, unleaded gasoline.

[DE] Geeignet für die Lieferung von industriellen Ölen und Treibstoffen, unverbleites Benzin.

[ES] Adecuado para la entrega de aceites y combustibles industriales, gasolina sin plomo

[FR] Convient pour la livraison d'huiles et de combustibles industriels, essence sans plomb



## STRUCTURE - AUFBAU - ESTRUCTURA - STRUCTURE

[EN] **Construction:** transparent pvc compound tube, one wire syntetic textile braid reinforcement

**Cover:** black pvc compound cover.

[DE] **Konstruktion:** Transparente PVC-Verbundrohr, ein Draht synthetische Textilgeflechtverstärkung **Decke:** schwarze PVC-Verbundabdeckung

[ES] **Construcción:** Tubo compuesto transparente del pvc, un refuerzo de la trenza del tejido sintético del alambre **Cobertura:** cubierta negra del compuesto del pvc

[FR] **Construction :** tuyau composé de pvc transparent, un renfort de tressage en textile synthétique,

**Revetement:** revêtement en pvc noir

mm	mm	bar	bar	gr/mt	m
5	10.5	10	30	80	25
6	11	10	30	80	25
8	14	10	30	110	25
10	16	10	30	140	25
19	26	10	30	320	25
25	33	10	30	473	25



## RECOMMENDED CLAMP/COLLAR - EMPFOHLENE KLAMMER/KRAGEN - ABRAZADERA/COLLAR RECOMENDADO - COLLIER/COLLIER RECOMMANDÉ



-5°C / +70°C  
+23°F / +140°F



**NORM.:** ISO 1307  
**MARKING:** Presscord Green Fuel Iso 1307