

AGROCONN PVC 50 BAR



APPLICATION - ANWENDUNG - USO - APPLICATION

[EN] for spraying of pesticides and fertilizers in agriculture

[DE] geeignet als schadlingsbekämpfungsschlauch im hochdruckbereich.

[ES] idóneo para equipo de motobombas irrigacion agrícola con insecticidas, pesticidas y antiparasitarios.

[FR] pour pulvérisation agricole



STRUCTURE - AUFBAU - ESTRUCTURA - STRUCTURE

[EN] **Tube:** special pvc compound resistant to pesticides and fertilizers.

Reinforcement: high tensile synthetic textile.

Cover: abrasion, ozone and weather resistant special pvc compound..

[DE] **Seele:** spezielle pvc-mischung, beständig gegen schädlingbekämpfungsmittel und dünger.

Einlagen: hochfestes synthetisches textildgewebe.

Decke: abriebfeste, ozon- und witterungsbeständige, spezielle pvc-mischung.







[ES] **Sustrato:** mezcla especial en pvc resistente al paso de anticriptogámicos y fertilizantes. **Refuerzo:** inserciones textiles con alta resistencia.

Cobertura: mezcla especial en pvc resistente a la abrasión, ozono y agentes atmosféricos.

[FR] **Construction:** tuyau lisse et flexible en pvc souple resistant aux engrais et pesticides.

Renforcement: insertion textile haute tenacite.

Revetement: lisse, en matiere pvc speciale resistente a l'abrasion, aux agents atmospheriques et a la plupart des produits chimiques

					
mm	mm	bar	bar	gr/mt	mt
8	14,5	50	150	175	100
10	17	50	150	217	100



RECOMMENDED CLAMP/COLLAR - EMPFOHLENE KLAMMER/KRAGEN - ABRAZADERA/COLLAR RECOMENDADO - COLLIER/COLLIER RECOMMANDÉ

STF – hose clamp with screw
SGT – Step less



-10°C / +60°C
+14°F / +140°F



NORM.: ISO 1307