


**F68OMX Swivel male stud**

Triple-Lok® 37° Flare female swivel end / Male metric thread O-ring + retaining ring



Tube O.D. mm	Tube O.D. in.	Thread Metric T8	Thread UN/UNF-2B T6	C4 mm	C3 mm	D mm	D2 mm	L5 mm	LL mm	Weight (steel) g/1 piece	Triple-Lok® Steel	PN (bar)
6	1/4	M 10×1.0	7/16-20	14	14	4.4	4.0	32	15.0	28	<b>4M10F68OMXS</b>	350
8	5/16	M 12×1.5	1/2-20	17	17	6.0	6.0	37	18.0	32	<b>5M12F68OMXS</b>	420
10	3/8	M 14×1.5	9/16-18	19	19	7.5	7.0	38	19.5	42	<b>6M14F68OMXS</b>	350
12	1/2	M 16×1.5	3/4-16	22	22	9.9	7.5	44	23.0	62	<b>8M16F68OMXS</b>	350
12	1/2	M 18×1.5	3/4-16	24	22	9.9	11.0	45	23.0	62	<b>8M18F68OMXS</b>	250
14, 15, 16	5/8	M 18×1.5	7/8-14	24	27	12.3	11.0	48	25.0	127	<b>10M18F68OMXS</b>	250
14, 15, 16	5/8	M 22×1.5	7/8-14	27	27	12.3	14.0	49	25.0	155	<b>10M22F68OMXS</b>	250
18, 20	3/4	M 27×2.0	1 1/16-12	32	32	15.5	15.5	55	26.0	172	<b>12M27F68OMXS</b>	210
25	1	M 33×2.0	1 5/16-12	41	38	21.5	23.0	57	29.0	259	<b>16M33F68OMXS</b>	210
28, 30, 32	1 1/4	M 42×2.0	1 5/8-12	50	50	27.5	30.0	63	33.0	484	<b>20M42F68OMXS</b>	210

Steel, stainless steel and brass Triple-Lok® parts are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page K92.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.