Medium Pressure



Technical Description

The 5500 series has been manufactured according to the regulations and dimensions of the standard specification ISO 7241-1 A series. With the pressure eliminator, it is possible to establish connections with residual pressure (up to 200 bar). The pressure eliminator is available for both - coupling and the plug.

Advantages

Can be fitted with pressure eliminator to ensure effortless connection even with residual

High flow performance (low pressure drop).

Working Pressure

See charts.

Working Temperature

-30°C up to +100°C (NBR) -25°C up to +200°C (FKM) depending on the medium. Special seals are available on request (see page 6).

Available Valves:



Applications Area




Bursting Pressure

Body Size	Bursting Pressure Connected							
1/2"	> 1000 bar							

Material Coupling	Standard / Pressure Eliminator							
Coupling Body	Brass							
Sleeve	Brass, nickel plated							
Valve	Brass hardened							
Springs	AISI 301							
Locking Balls	AISI 420 C							
Seals	NBR/FKM							
Valve Holder (up to 100°C)	Zinc Casting							
Valve Holder (over 100°C)	Brass							
Plug	Standard / Pressure Eliminator							
Coupling Body	Steel hardened, zinc plated, passivated							
Valve	Brass, hardened							
Springs	AISI 301							
Seals	NBR/FKM							
Valve Holder (up to 100°C)	Zinc Casting							
Valve Holder (over 100°C)	Brass							

Flow Capacity with Oil with Viscosity of 32cSt at 40°C as per ISO 7241/2-2000



5500-Series **Couplings** Body Connection Working Pressure D Seal Part Number Hex L Size Α mm mm mm connected in bar 1/2" G 1/2 NBR 5510 27 250 1/2" G 1/2 27 63 38 250 FKM 5510 V

Female Thread

Plugs								5500-Series
	Body Size	Connection A	Hex mm	L mm	D mm	Working Pressure connected in bar	Seal	Part Number
	1/2"	G 1/2	27	42	20	250	NBR	5520
HEX	1/2"	G 1/2	27	42	20	250	FKM	5520 V
Face de Thomas								
Female Thread								

Couplings 5500-Series Pressure Eliminator Hex D Working Pressure Body Connection L Seal Part Number Size connected in bar mm mm mm Α 5511 1/2" G 1/2 27 63 38 250 **NBR** 1/2" G 1/2 27 63 38 250 FKM 5511 V Female Thread

Plugs			5500-Series Pressure Eliminator						
		Body Size	Connection A	Hex mm	L mm	D mm	Working Pressure connected in bar	Seal	Part Number
	HEX	1/2"	G 1/2	27	42	20	250	NBR	5521
		1/2"	G 1/2	27	42	20	250	FKM	5521 V
Fomale	Throad								
remaie	Female Thread								

Seal-Kit				5500-Series
	Body Size	Version	Material	Part Number
	1/2"	for coupling	NBR	5500-PSN
	1/2"	for coupling	FKM	5500-PSV
	1/2"	for coupling	EPDM	5500-PSEP

Dust Protection							5500-Series
	Body Size	Version	L mm	D mm	Material	Color	Part Number
	1/2"	for coupling	242	30	PVC	Blue	5515-QC
	1/2"	for plug	264	30	PVC	Blue	5525

