


## JMTX Union tee

Triple-Lok® 37° Flare end (three ends)  
SAE 070401 MS51510



Tube O.D. mm	in.	Thread UN/UNF-2A T	D mm	M mm	Y mm	Weight (steel) g/1 piece	Triple-Lok®	Triple-Lok®	Triple-Lok®	PN (bar)	
							Steel	Stainless Steel	Brass	S	SS
6	1/8	5/16-24	1.6	19.5	8.0	25	<b>2 JTX-S</b>			500	—
	3/16	3/8-24	3.0	21.0	11.0	30	<b>3 JTX-S</b>			500	—
	1/4	7/16-20	4.4	22.5	11.0	33	<b>4JMTXS</b>	<b>4JMTXSS</b>	<b>4 JTX-B</b>	500	350
	5/16	1/2-20	6.0	24.0	13.0	42	<b>5JMTXS</b>	<b>5JMTXSS</b>	<b>5 JTX-B</b>	420	350
	3/8	9/16-18	7.5	27.0	14.0	53	<b>6JMTXS</b>	<b>6JMTXSS</b>	<b>6 JTX-B</b>	420	350
	12	1/2	3/4-16	9.9	32.0	19.0	118	<b>8JMTXS</b>	<b>8JMTXSS</b>	<b>8 JTX-B</b>	420
14, 15, 16	5/8	7/8-14	12.3	37.0	22.0	182	<b>10JMTXS</b>	<b>10JMTXSS</b>	<b>10 JTX-B</b>	350	350
18, 20	3/4	1 1/16-12	15.5	42.0	27.0	291	<b>12JMTXS</b>	<b>12JMTXSS</b>	<b>12 JTX-B</b>	350	350
22	7/8	1 3/16-12	18.0	45.8	33.0	403	<b>14 JTX-S</b>	<b>14JMTXSS</b>	<b>14 JTX-B</b>	280	245
25	1	1 5/16-12	21.5	46.0	33.0	415	<b>16JMTXS</b>	<b>16JMTXSS</b>	<b>16 JTX-B</b>	280	280
28, 30, 32	1 1/4	1 5/8-12	27.5	52.0	41.0	706	<b>20JMTXS</b>	<b>20JMTXSS</b>	<b>20 JTX-B</b>	280	210
35, 38	1 1/2	1 7/8-12	33.0	59.0	48.0	990	<b>24 JTX-S</b>	<b>24JMTXSS</b>	<b>24 JTX-B</b>	210	140
42	1 3/4	2 1/4-12	39.0	74.5	63.0	2270	<b>28 JTX-S</b>			140	—
	2	2 1/2-12	45.0	78.0	63.5	2450	<b>32 JTX-S</b>			140	—

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.

For Brass parts reduce pressures by 35%.

Union tee reducing up on request.

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

K