


## FNML Cap

O-Lok® ORFS Female swivel cap end  
SAE 520112



Thread UN/UNF-2B T6	B mm	K mm	L5 mm	Weight (steel) g/1 piece	O-Lok® Steel	O-Lok® Stainless Steel		PN (bar)	
								S	SS
9/16-18	17	9	16	6	<b>4FNMLS</b>	<b>4FNMLSS</b>	630	630	
11/16-16	22	11	20	10	<b>6FNMLS</b>	<b>6FNMLSS</b>	630	630	
13/16-16	24	12	22	11	<b>8FNMLS</b>	<b>8FNMLSS</b>	630	630	
1-14	30	14	26	31	<b>10FNMLS</b>	<b>10FNMLSS</b>	420	420	
1 3/16-12	36	15	29	52	<b>12FNMLS</b>	<b>12FNMLSS</b>	420	420	
1 7/16-12	41	16	30	81	<b>16FNMLS</b>	<b>16FNMLSS</b>	420	420	
1 11/16-12	48	16	30	129	<b>20 FNL-S</b>	<b>20FNMLSS</b>	280	280	
2-12	57	16	30	189	<b>24 FNL-S</b>	<b>24FNMLSS</b>	280	280	

Part numbers shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.