


PNMTX Plug

Triple-Lok® 37° Flare end plug
SAE 070109 MS51518



Tube O.D. mm	in.	Thread UN/UNF-2A T	C mm	L mm	Weight (steel) g/1 piece	Triple-Lok® Steel	Triple-Lok® Stainless Steel		PN (bar)	
							S	SS	S	SS
6	1/8	5/16-24	11.00	18	9	2 PNTX-S			500	—
	3/16	3/8-24	11.00	19	10	3 PNTX-S			500	—
	1/4	7/16-20	13.00	21	10	4PNMTXS	4PNMTXSS	500	350	
	5/16	1/2-20	14.00	21	14	5PNMTXS	5PNMTXSS	420	350	
	3/8	9/16-18	16.00	21	19	6 PNTX-S	6PNMTXSS	420	350	
14, 15, 16	1/2	3/4-16	19.00	24	39	8PNMTXS	8PNMTXSS	420	350	
	5/8	7/8-14	24.00	28	60	10PNMTXS	10PNMTXSS	350	350	
	3/4	1 1/16-12	27.00	33	93	12PNMTXS	12PNMTXSS	350	350	
	7/8	1 3/16-12	31.75	33	95	14 PNTX-S	14PNMTXSS	280	280	
	1	1 5/16-12	35.00	34	98	16 PNTX-S	16PNMTXSS	280	280	
28, 30, 32	1 1/4	1 5/8-12	42.80	37	269	20 PNTX-S	20PNMTXSS	280	210	
	1 1/2	1 7/8-12	51.00	42	360	24 PNTX-S	24PNMTXSS	210	140	
35, 38	2	2 1/2-12	66.60	52	470	32 PNTX-S		140	—	

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

K