


## P50NM Hexagon head plug

Male UN/UNF thread – O-ring (ISO 11926)  
SAE 090109A



Thread UN/UNF-2A T5	C4 mm	D2 mm	I1 mm	L mm	L2 mm	Weight (steel) g/1 piece	Adapter Steel	Adapter Stainless Steel	PN (bar)	
									S	SS
5/16-24	11.0	2.4	8	15	10	7	<b>2 P50N-S</b>	<b>2P50NMSS</b>	420	420
3/8-24	12.7	3.2	8	15	9	9	<b>3 P50N-S</b>	<b>3P50NMSS</b>	420	420
7/16-20	14.3	5.2	9	17	10	13	<b>4 P50N-S</b>	<b>4P50NMSS</b>	420	420
1/2-20	16.0	5.9	9	17	10	19	<b>5 P50N-S</b>	<b>5P50NMSS</b>	420	420
9/16-18	17.5	7.5	10	19	11	22	<b>6 P50N-S</b>	<b>6P50NMSS</b>	420	420
3/4-16	22.2	10.7	11	20	11	44	<b>8 P50N-S</b>	<b>8P50NMSS</b>	420	420
7/8-14	25.4	12.7	13	24	12	53	<b>10 P50N-S</b>	<b>10P50NMSS</b>	420	420
1 1/16-12	31.8	16.7	15	28	15	117	<b>12 P50N-S</b>	<b>12P50NMSS</b>	420	420
1 3/16-12	35.0	18.2	15	28	14	124	<b>14 P50N-S</b>	<b>14P50NMSS</b>	380	380
1 5/16-12	38.0	22.2	15	28	13	141	<b>16 P50N-S</b>	<b>16P50NMSS</b>	380	380
1 5/8-12	47.6	27.8	15	31	10	284	<b>20 P50N-S</b>	<b>20P50NMSS</b>	280	280
1 7/8-12	54.0	34.1	15	32	9	447	<b>24 P50N-S</b>	<b>24P50NMSS</b>	210	210
2 1/2-12	70.0	46.1	15	36	14	807	<b>32 P50N-S</b>	<b>32P50NMSS</b>	140	140

Parker Adapter are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page N60.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

N