


Pressure Regulator Fittings

7300 Pressure Regulator, Male BSPP Thread

Technical polymer, Nickel-plated brass, NBR



ØD	C		E	F1	F2	G1	G2	H max	L1	L2	Kg
4	G1/8	7300 04 10	4.5	17	13	14	17	65	7	18.5	0.047
	G1/8	7300 06 10	4.5	17	13	14	17	65	7	20	0.047
6	G1/4	7300 06 13	7.5	17	13	14	17	74.5	9.5	22	0.065
	G1/8	7300 08 10	4.5	17	13	14	17	65	7	25	0.048
8	G1/4	7300 08 13	7.5	17	13	14	17	74.5	9.5	27	0.066
	G3/8	7300 08 17	8.5	22	17	18.5	22	84	11.5	28.5	0.122
10	G1/4	7300 10 13	7.5	17	13	14	17	74.5	9.5	29	0.066
	G3/8	7300 10 17	8.5	22	17	18.5	22	84	11.5	30.5	0.122

DRV Pressure Reducing Valve

Brass



A	A1		HEX	L	L1	Inlet Pressure	Outlet Pressure *
G1/4	G1/4	DRV13/20	17	34	9	15 bar	2.6 bar
G1/4	G1/4	DRV13/30	17	34	9	15 bar	3.7 bar
G1/4	G1/4	DRV13/40	17	34	9	15 bar	4.5 bar
G1/4	G1/4	DRV13/50	17	34	9	15 bar	5.4 bar
G1/4	G1/4	DRV13/60	17	34	9	15 bar	6.2 bar
G1/4	G1/4	DRV13/70	17	34	9	15 bar	8 bar
G1/4	G1/4	DRV13/80	17	34	9	15 bar	8.2 bar
G1/4	G1/4	DRV13/100	17	34	9	15 bar	10.2 bar

* Tolerance outlet pressure +/- 0.5 bar