


1C658 – Metric female swivel 24°/60° Heavy series – Metric swivel nut




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN	size	mm	inch	Connection type		A mm	B mm	H mm	J mm	Max. WP MPa
					Thread size	Tube OD mm					
1C658-8-3	5	-03	4.8	3/16	M16x1.5	8	53	28	17	19	63.0
1C658-10-4	6	-04	6.4	1/4	M18x1.5	10	60	28	19	22	63.0
1C658-12-5	8	-05	7.9	5/16	M20x1.5	12	64	32	22	24	63.0
1C658-12-6	10	-06	9.5	3/8	M20x1.5	12	69	32	22	24	63.0
1C658-14-6	10	-06	9.5	3/8	M22x1.5	14	66	30	24	27	63.0
1C658-14-8	12	-08	12.7	1/2	M22x1.5	14	71	30	24	27	63.0
1C658-16-8	12	-08	12.7	1/2	M24x1.5	16	72	31	27	30	40.0
1C658-20-12	20	-12	19.0	3/4	M30x2	20	84	38	32	36	40.0
1C658-25-12	20	-12	19.0	3/4	M36x2	25	82	36	36	46	40.0
1C658-30-16	25	-16	25.4	1	M42x2	30	102	42	38	50	25.0

58 series

1CA58 – Metric female swivel 24° with O-ring Light series – Metric swivel nut – ISO 12151-2




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN	size	mm	inch	Connection type		A mm	B mm	H mm	J mm	Max. WP MPa
					Thread size	Tube OD mm					
1CA58-6-3	5	-03	4.8	3/16	M12x1.5	6	54	29	14	14	31.5
1CA58-8-4	6	-04	6.4	1/4	M14x1.5	8	60	29	17	19	42.5
1CA58-10-5	8	-05	7.9	5/16	M16x1.5	10	62	30	19	19	40.0
1CA58-12-5	8	-05	7.9	5/16	M18x1.5	12	63	31	19	22	35.0
1CA58-10-6	10	-06	9.5	3/8	M16x1.5	10	67	31	19	19	40.0
1CA58-12-6	10	-06	9.5	3/8	M18x1.5	12	68	31	19	22	35.0
1CA58-15-8	12	-08	12.7	1/2	M22x1.5	15	74	33	24	27	31.5
1CA58-18-10	16	-10	15.9	5/8	M26x1.5	18	80	35	27	32	31.5
1CA58-18-12	20	-12	19.0	3/4	M26x1.5	18	80	34	32	32	31.5
1CA58-22-12	20	-12	19.0	3/4	M30x2	22	80	34	32	36	28.0
1CA58-28-16	25	-16	25.4	1	M36x2	28	101	41	36	46	21.0

1C958 – Metric female swivel 24° with O-ring

Heavy series – Metric swivel nut – ISO 12151-2




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type Thread size	Tube OD mm	A mm	B mm	H mm	J mm	Max. WP MPa	
	mm	inch	inch								
1C958-8-3	5	-03	4.8	3/16	M16x1.5	8	54	29	17	19	63.0
1C958-10-4	6	-04	6.4	1/4	M18x1.5	10	67	36	17	22	63.0
1C958-12-5	8	-05	7.9	5/16	M20x1.5	12	63	32	19	24	63.0
1C958-12-6	10	-06	9.5	3/8	M20x1.5	12	68	32	19	24	63.0
1C958-14-6	10	-06	9.5	3/8	M22x1.5	14	70	33	24	27	63.0
1C958-16-8	12	-08	12.7	1/2	M24x1.5	16	77	36	24	30	42.0
1C958-20-10	16	-10	15.9	5/8	M30x2	20	83	38	30	36	42.0
1C958-20-12	20	-12	19.0	3/4	M30x2	20	84	38	30	36	42.0
1C958-25-12	20	-12	19.0	3/4	M36x2	25	88	42	36	46	42.0
1C958-30-16	25	-16	25.4	1	M42x2	30	104	44	41	50	42.0

1CE58 – Metric female swivel 24° with O-ring


45° elbow – Light series – Metric swivel nut – ISO 12151-2



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type Thread size	Tube OD mm	A mm	B mm	E mm	J mm	Max. WP MPa	
	mm	inch	inch								
1CE58-6-3	5	-03	4.8	3/16	M12x1.5	6	67	42	16	14	31.5
1CE58-8-4	6	-04	6.4	1/4	M14x1.5	8	75	43	18	19	42.5
1CE58-10-5	8	-05	7.9	5/16	M16x1.5	10	75	44	18	19	40.0
1CE58-10-6	10	-06	9.5	3/8	M16x1.5	10	83	46	19	19	40.0
1CE58-12-6	10	-06	9.5	3/8	M18x1.5	12	83	46	19	22	35.0
1CE58-15-8	12	-08	12.7	1/2	M22x1.5	15	92	51	21	27	31.5
1CE58-18-10	16	-10	15.9	5/8	M26x1.5	18	101	56	23	32	31.5
1CE58-18-12	20	-12	19.0	3/4	M26x1.5	18	108	62	25	32	31.5
1CE58-22-12	20	-12	19.0	3/4	M30x2	22	108	62	26	36	28.0

10C58 – Metric female swivel 24° with O-ring
45° elbow – Heavy series – Metric swivel nut – ISO 12151-2




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Tube OD mm							
10C58-8-3	5	-03	4.8	3/16	M16x1.5	8	68	43	18	19	63.0
10C58-16-8	12	-08	12.7	1/2	M24x1.5	16	93	52	23	30	42.0

58 series


1CF58 – Metric female swivel 24° with O-ring
90° elbow – Light series – Metric swivel nut – ISO 12151-2



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Tube OD mm							
1CF58-6-3	5	-03	4.8	3/16	M12x1.5	6	55	30	29	14	31.5
1CF58-8-4	6	-04	6.4	1/6	M14x1.5	8	64	32	32	19	42.5
1CF58-10-5	8	-05	7.9	5/16	M16x1.5	10	65	33	32	19	40.0
1CF58-10-6	10	-06	9.5	3/8	M16x1.5	10	73	36	35	19	40.0
1CF58-12-6	10	-06	9.5	3/8	M18x1.5	12	73	36	35	22	35.0
1CF58-15-8	12	-08	12.7	1/2	M22x1.5	15	82	41	42	27	31.5
1CF58-18-10	16	-10	15.9	5/8	M26x1.5	18	91	46	46	32	31.5
1CF58-18-12	20	-12	19.0	3/4	M26x1.5	18	100	54	54	32	31.5
1CF58-22-12	20	-12	19.0	3/4	M30x2	22	100	54	52	36	28.0
1CF58-28-16	25	-16	25.4	1	M36x2	28	122	62	65	46	21.0


11C58 – Metric female swivel 24° with O-ring 90° elbow – Heavy series – Metric swivel nut – ISO 12151-2



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Tube OD mm							
11C58-12-5	8	-05	7.9	5/16	M20x1.5	12	65	33	34	24	63.0
11C58-12-6	10	-06	9.5	3/8	M20x1.5	12	73	36	37	24	63.0
11C58-16-8	12	-08	12.7	1/2	M24x1.5	16	82	41	44	30	42.0

1D058 – Metric male 24° Light series – ISO 12151-2




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	H mm	Max. WP MPa
	mm	inch	Thread size	Tube OD mm						
1D058-6-3	5	-03	4.8	3/16	M12x1.5	6	49	23	17	25.0
1D058-8-4	6	-04	6.4	1/4	M14x1.5	8	55	23	19	42.5
1D058-10-5	8	-05	7.9	5/16	M16x1.5	10	58	26	19	40.0
1D058-12-5	8	-05	7.9	5/16	M18x1.5	12	59	27	19	35.0
1D058-10-6	10	-06	9.5	3/8	M16x1.5	10	63	26	22	40.0
1D058-12-6	10	-06	9.5	3/8	M18x1.5	12	64	27	22	35.0
1D058-15-6	10	-06	9.5	3/8	M22x1.5	15	67	30	27	31.0
1D058-15-8	12	-08	12.7	1/2	M22x1.5	15	71	30	27	31.0
1D058-18-12	20	-12	19.0	3/4	M26x1.5	18	76	30	32	28.0
1D058-22-12	20	-12	19.0	3/4	M30x2	22	77	31	36	28.0
1D058-28-16	25	-16	25.4	1	M36x2	28	91	31	41	21.0

1D258 – Metric male 24°


Heavy series – ISO 12151-2



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN	size	mm		inch		Connection type		A mm	B mm	H mm	Max. WP MPa
			mm	inch	Thread size	Tube OD mm						
1D258-8-3	5	-03	4.8	3/16	M16x1.5	8	52	27	19	63.0		
1D258-10-4	6	-04	6.4	1/4	M18x1.5	10	58	26	22	63.0		
1D258-12-5	8	-05	7.9	5/16	M20x1.5	12	62	30	24	63.0		
1D258-14-6	10	-06	9.5	3/8	M22x1.5	14	69	32	27	63.0		
1D258-16-8	12	-08	12.7	1/2	M24x1.5	16	73	32	27	42.0		
1D258-20-12	20	-12	19.0	3/4	M30x2	20	79	33	36	42.0		
1D258-25-12	20	-12	19.0	3/4	M36x2	25	81	35	41	42.0		
1D258-30-16	25	-16	25.4	1	M42x2	30	95	35	46	42.0		

19258 – BSP female swivel 60° cone




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN	size	mm		inch		Connection type		A mm	B mm	H mm	J mm	Max. WP MPa
			mm	inch	Thread size	Tube OD inch							
19258-4-3	5	-03	4.8	3/16	G 1/4	1/4	53	28	17	19	63.0		
19258-4-4	6	-04	6.4	1/4	G 1/4	1/4	58	26	17	19	63.0		
19258-6-5	8	-05	7.9	5/16	G 3/8	3/8	59	27	19	22	55.0		
19258-6-6	10	-06	9.5	3/8	G 3/8	3/8	64	27	19	22	55.0		
19258-8-8	12	-08	12.7	1/2	G 1/2	1/2	72	31	24	27	43.0		
19258-10-8	12	-08	12.7	1/2	G 5/8	5/8	75	34	27	30	37.5		
19258-12-12	20	-12	19.0	3/4	G 3/4	3/4	81	35	32	32	35.0		
19258-16-16	25	-16	25.4	1	G 1	1	99	39	36	41	28.0		

58 series


1B258 – BSP female swivel 60° cone 90° elbow



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Tube OD inch							
1B258-4-4	6	-04	6.4	1/4	G 1/4	1/4	64	32	28	19	63.0
1B258-6-5	8	-05	7.9	5/16	G 3/8	3/8	65	33	30	22	55.0
1B258-6-6	10	-06	9.5	3/8	G 3/8	3/8	73	36	33	22	55.0
1B258-8-8	12	-08	12.7	1/2	G 1/2	1/2	82	41	40	27	43.0
1B258-10-8	12	-08	12.7	1/2	G 5/8	5/8	82	41	38	30	37.5
1B258-12-12	20	-12	19.0	3/4	G 3/4	3/4	100	54	53	32	35.0
1B258-16-16	25	-16	25.4	1	G 1	1	127	67	65	41	28.0


1D958 – BSP male DIN 3852 Form A



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	H mm	Max. WP MPa
	mm	inch	Thread size	Tube OD inch						
1D958-4-4	6	-04	6.4	1/4	G 1/4	1/4	58	26	19	63.0
1D958-6-5	8	-05	7.9	5/16	G 3/8	3/8	59	27	22	55.0
1D958-6-6	10	-06	9.5	3/8	G 3/8	3/8	64	27	22	55.0
1D958-8-8	12	-08	12.7	1/2	G 1/2	1/2	72	31	27	43.0
1D958-12-12	20	-12	19.0	3/4	G 3/4	3/4	80	34	32	35.0
1D958-16-16	25	-16	25.4	1	G 1	1	95	35	41	28.0

10158 – National Pipe Tapered (NPT) male




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type		Tube OD inch	A mm	B mm	H mm	Max. WP MPa
	mm	inch	inch	Thread size	Thread size					
10158-2-3	5	-03	4.8	3/16	1/8 - 27NPTF	1/8	51	26	14	34.5
10158-4-3	5	-03	4.8	3/16	1/4 - 18NPTF	1/4	55	30	17	34.5
10158-6-3	5	-03	4.8	3/16	3/8 - 18NPTF	3/8	54	29	19	27.5
10158-2-4	6	-04	6.4	1/4	1/8 - 27NPTF	1/8	54	22	17	34.5
10158-4-4	6	-04	6.4	1/4	1/4 - 18NPTF	1/4	62	30	17	34.5
10158-6-4	6	-04	6.4	1/4	3/8 - 18NPTF	3/8	61	29	19	27.5
10158-4-5	8	-05	7.9	5/16	1/4 - 18NPTF	1/4	59	27	17	34.5
10158-6-5	8	-05	7.9	5/16	3/8 - 18NPTF	3/8	61	29	19	27.5
10158-4-6	10	-06	9.5	3/8	1/4 - 18NPTF	1/4	66	30	19	34.5
10158-6-6	10	-06	9.5	3/8	3/8 - 18NPTF	3/8	70	33	19	27.5
10158-8-6	10	-06	9.5	3/8	1/2 - 14NPTF	1/2	77	40	27	24.0
10158-6-8	12	-08	12.7	1/2	3/8 - 18NPTF	3/8	71	30	22	27.5
10158-8-8	12	-08	12.7	1/2	1/2 - 14NPTF	1/2	77	36	27	24.0
10158-12-12	20	-12	19.0	3/4	3/4 - 14NPTF	3/4	82	36	30	21.0
10158-16-16	25	-16	25.4	1	1 - 11 1/2NPTF	1	104	44	41	17.0

58 series


10658 – SAE (JIC) 37° female swivel UNF swivel nut



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
For stainless steel (AISI 316) please add **C** to the Part No. Example: 10658-4-3C.
Other materials available on request.

Part No. #	DN size mm inch			Connection type		Tube OD inch	A mm	B mm	H mm	J mm	Max. WP MPa
	mm	inch	inch	Thread size	Thread size						
10658-4-3	5	-03	4.8	3/16	7/16 - 20UNF	1/4	55	30	16	17	41.0
10658-5-3	5	-03	4.8	3/16	1/2 - 20UNF	5/16	57	32	16	17	41.0
10658-4-4	6	-04	6.4	1/4	7/16 - 20UNF	1/4	65	33	17	17	41.0
10658-5-4	6	-04	6.4	1/4	1/2 - 20UNF	5/16	65	33	16	17	41.0
10658-6-4	6	-04	6.4	1/4	9/16 - 18UNF	3/8	67	35	17	19	34.5
10658-5-5	8	-05	7.9	5/16	1/2 - 20UNF	5/16	65	33	16	17	41.0
10658-6-5	8	-05	7.9	5/16	9/16 - 18UNF	3/8	65	33	16	19	34.5
10658-6-6	10	-06	9.5	3/8	9/16 - 18UNF	3/8	69	33	19	19	34.5
10658-8-6	10	-06	9.5	3/8	3/4 - 16UNF	1/2	72	35	19	24	34.5
10658-6-8	12	-08	12.7	1/2	9/16 - 18UNF	3/8	76	35	22	19	34.5
10658-8-8	12	-08	12.7	1/2	3/4 - 16UNF	1/2	79	38	22	22	34.5
10658-10-8	12	-08	12.7	1/2	7/8 - 14UNF	5/8	82	41	22	27	34.5
10658-12-8	12	-08	12.7	1/2	1 1/16 - 12UNF	3/4	83	42	27	32	34.5
10658-12-12	20	-12	19.0	3/4	1 1/16 - 12UNF	3/4	88	42	30	32	34.5
10658-16-12	20	-12	19.0	3/4	1 5/16 - 12UNF	1	90	44	36	38	27.5
10658-16-16	25	-16	25.4	1	1 5/16 - 12UNF	1	104	44	36	38	27.5

13958 – SAE (JIC) 37° female swivel 90° elbow – UNF swivel nut




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type		Tube OD inch	A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Thread size							
13958-4-3-SM	5	-03	4.8	3/16	7/16 - 20UNF	1/4	55	30	21	17	41.0
13958-4-4-SM	6	-04	6.4	1/4	7/16 - 20UNF	1/4	64	32	21	17	41.0
13958-5-4-SM	6	-04	6.4	1/4	1/2 - 20UNF	5/16	64	32	25	17	41.0
13958-6-4-SM	6	-04	6.4	1/4	9/16 - 18UNF	3/8	64	32	22	19	34.5
13958-6-5-SM	8	-05	7.9	5/16	9/16 - 18UNF	3/8	65	33	22	19	34.5
13958-6-6-SM	10	-06	9.5	3/8	9/16 - 18UNF	3/8	73	36	28	19	34.5
13958-8-6-SM	10	-06	9.5	3/8	3/4 - 16UNF	1/2	71	34	29	22	34.5
13958-8-8-SM	12	-08	12.7	1/2	3/4 - 16UNF	1/2	77	36	29	22	34.5
13958-10-8-SM	12	-08	12.7	1/2	7/8 - 14UNF	5/8	77	36	32	27	34.5
13958-12-12-SM	20	-12	19.0	3/4	1 1/16 - 12UNF	3/4	97	51	46	32	34.5
13958-16-16-SM	25	-16	25.4	1	1 5/16 - 12UNF	1	121	61	55	41	27.5

58 series

1JC58 – O-Lok® ORFS swivel nut Short version – UNF swivel nut – ISO 12151-1




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type		Tube OD inch	A mm	B mm	H mm	J mm	Max. WP MPa
	mm	inch	Thread size	Thread size							
1JC58-4-3-SM	5	-03	4.8	3/16	9/16 - 18UNF	1/4	47	22	17	17	41.0
1JC58-4-4-SM	6	-04	6.4	1/4	9/16 - 18UNF	1/4	53	22	17	17	41.0
1JC58-6-4-SM	6	-04	6.4	1/4	11/16 - 16UNF	3/8	59	27	19	22	41.0
1JC58-4-5-SM	8	-05	7.9	5/16	9/16 - 18UNF	1/4	53	22	17	17	41.0
1JC58-6-5-SM	8	-05	7.9	5/16	11/16 - 16UNF	3/8	56	25	19	22	41.0
1JC58-6-6-SM	10	-06	9.5	3/8	11/16 - 16UNF	3/8	61	25	19	22	41.0
1JC58-8-6-SM	10	-06	9.5	3/8	13/16 - 16UNF	1/2	63	27	22	24	41.0
1JC58-8-8-SM	12	-08	12.7	1/2	13/16 - 16UNF	1/2	69	27	24	24	41.0
1JC58-10-8-SM	12	-08	12.7	1/2	1 - 14UNF	5/8	73	32	30	30	41.0
1JC58-12-12-SM	20	-12	19.0	3/4	1 3/16 - 12UNF	3/4	79	33	32	36	41.0
1JC58-16-16-SM	25	-16	25.4	1	1 7/16 - 12UNF	1	96	36	36	41	41.0

1JS58 – O-Lok® ORFS swivel nut

Long version – UNF swivel nut – ISO 12151-1




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type		Tube OD inch	A mm	B mm	H mm	J mm	Max. WP MPa
	mm	inch	Thread size	Thread size							
1JS58-4-3-SM	5	-03	4.8	3/16	9/16 - 18UNF	1/4	60	35	17	17	41.0
1JS58-4-4-SM	6	-04	6.4	1/4	9/16 - 18UNF	1/4	67	35	17	17	41.0
1JS58-6-4-SM	6	-04	6.4	1/4	11/16 - 16UNF	3/8	66	35	19	22	41.0
1JS58-4-5-SM	8	-05	7.9	5/16	9/16 - 18UNF	1/4	67	35	17	17	41.0
1JS58-6-5-SM	8	-05	7.9	5/16	11/16 - 16UNF	3/8	66	35	19	22	41.0
1JS58-6-6-SM	10	-06	9.5	3/8	11/16 - 16UNF	3/8	71	35	19	22	41.0
1JS58-8-6-SM	10	-06	9.5	3/8	13/16 - 16UNF	1/2	75	38	22	24	41.0
1JS58-8-8-SM	12	-08	12.7	1/2	13/16 - 16UNF	1/2	80	38	22	24	41.0
1JS58-10-10-SM	16	-10	15.9	5/8	1 - 14UNF	5/8	90	44	30	30	41.0
1JS58-12-12-SM	20	-12	19.0	3/4	1 3/16 - 12UNF	3/4	94	48	32	36	41.0
1JS58-16-16-SM	25	-16	25.4	1	1 7/16 - 12UNF	1	112	52	36	41	41.0

1J758 – O-Lok® ORFS swivel nut

45° elbow – UNF swivel nut – ISO 12151-1




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size			Connection type		Tube OD inch	A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Thread size							
1J758-4-4	6	-04	6.4	1/4	9/16 - 18UNF	5/16	71	39	10	17	41.0
1J758-6-4	6	-04	6.4	1/4	11/16 - 16UNF	3/8	73	41	12	22	41.0
1J758-6-6	10	-06	9.5	3/8	11/16 - 16UNF	3/8	78	41	14	22	41.0
1J758-8-6	10	-06	9.5	3/8	13/16 - 16UNF	1/2	78	42	14	24	41.0
1J758-8-8	12	-08	12.7	1/2	13/16 - 16UNF	1/2	83	42	12	24	41.0
1J758-12-12	20	-12	19.0	3/4	1 3/16 - 12UNF	3/4	103	57	21	36	41.0
1J758-16-16	25	-16	25.4	1	1 7/16 - 12UNF	1	130	70	26	41	41.0

1J958 – O-Lok® ORFS swivel nut

90° elbow – UNF swivel nut – ISO 12151-1



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
Other materials available on request.

Part No. #	DN size				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	mm	inch	Thread size	Tube OD inch							
1J958-4-4	6	-04	6.4	1/4	9/16 - 18UNF	1/4	67	35	21	17	41.0
1J958-6-4	6	-04	6.4	1/4	11/16 - 16UNF	3/8	68	36	23	22	41.0
1J958-6-5	8	-05	7.9	5/16	11/16 - 16UNF	3/8	67	35	23	22	41.0
1J958-6-6	10	-06	9.5	3/8	11/16 - 16UNF	3/8	72	36	29	22	41.0
1J958-8-8	12	-08	12.7	1/2	13/16 - 16UNF	1/2	82	41	29	24	41.0
1J958-12-12	20	-12	19.0	3/4	1 3/16 - 12UNF	3/4	100	54	47	36	41.0
1J958-16-16	25	-16	25.4	1	1 7/16 - 12UNF	1	128	68	64	41	41.0