

BRAID 304



10.5140.

Stainless steel braid AISI 304 / EN 1.4404

#	inch	ID mm	wire diameter mm	n ° of wires	carriers	braid angle	braid coverage %	KG
								kg/m
10.5140.006	1/4"	6,0	0,25	6	24	90	97,5	0,07
10.5140.008	5/16"	8,0	0,25	7	24	90	95,1	0,08
10.5140.010	3/8"	10,0	0,25	8	24	90	94,0	0,10
10.5140.013	1/2"	12,0	0,25	10	24	90	96,3	0,12
10.5140.016	5/8"	16,0	0,30	11	24	90	95,5	0,21
10.5140.020	3/4"	20,0	0,30	9	36	90	96,6	0,25
10.5140.025	1"	25,0	0,30	10	36	90	94,6	0,27
10.5140.032	1.1/4"	32,0	0,35	8	48	90	93,1	0,40
10.5140.040	1.1/2"	40,0	0,35	10	48	90	94,4	0,49
10.5140.050	2"	50,0	0,40	11	48	90	95,5	0,73
10.5140.065	2.1/2"	65,0	0,40	11	64	90	95,2	0,92
10.5140.075	3"	80,0	0,40	12	64	90	93,2	1,06
10.5140.100	4"	100,0	0,50	11	64	90	90,3	1,60
10.5140.125	5"	125,0	0,57	10	72	98	87,8	2,22
10.5140.150	6"	150,0	0,57	11	72	98	85	2,49
10.5140.200	8"	200,0	0,67	9	96	102	86,8	4,30
10.5140.250	10"	250,0	0,70	12	96	104	93,7	6,60

BRAID: 1 stainless steel wire braid

APPLICATION: steam, chemicals, oxygen, thermofluid, naphtha, cryogening

TEMPERATURE RANGE: -200°C (-328°F) +600°C (+1112°F)

COUPLINGS: Balflex® Welding Rings serie 31